



Inspectable
Polyester Round Slings
 U.S. Patent #747926

FP *Inspectable Roundsling*® supply Riggers with a consistent and reliable visual inspection of the core yarns.

- * Transparent Clear Cover® makes inspection of the load bearing core yarns a reality.
- * Durable two-ply Clear Cover® protects load bearing fibers.
- * Seamless – No stitched edges that can rupture prematurely.
- * Conforms to shape of load to grip easily.
- * Elongation approximately 3% at rated capacity.
- * Endless configuration allows for rotation of wear points.

Part Number	Vertical	Choker*	Basket**	Weight (lbs./ft.) approx.	Body Dia. Relaxed (in.)
FP 30	3,000	2,400	6,000	.25 lbs	2"
FP 60	6,000	4,800	12,000	.35 lbs	2"
FP 90	9,000	7,200	18,000	.50 lbs	2"
FP 120	12,000	9,600	24,000	.65 lbs	3"
FP 140	14,000	11,200	28,000	.70 lbs	3"
FP 170	17,000	13,600	34,000	.80 lbs	3"
FP 230	23,000	18,400	46,000	1.11 lbs	4"
FP 260	26,000	20,800	52,000	1.20 lbs	4"
FP 320	32,000	25,600	64,000	1.60 lbs	4"
FP 400	40,000	32,000	80,000	1.80 lbs	5"
FP 540	54,000	43,200	108,000	2.40 lbs	6"
FP 680	68,000	54,400	136,000	3.00 lbs	6"
FP 900	90,000	72,000	180,000	3.85 lbs	6"

*Choker hitch capacities are based on a choke angle greater than 120°.

**Basket capacities are based on a 90° basket hitch.

WARNING: Do not exceed rated capacities. All edges must be properly padded to avoid cutting cover and core yarns. Failure to follow proper inspection, care and use criteria may result in personal injury or death.