

UB500 Series Top Swiveling Overhaul Balls



All sizes are RFID EQUIPPED



With **S320**
Eye Hook



With **S1316 A**
SHUR-LOC®
Eye Hook



Both styles available with optional **McKissick®** Wedge Socket Assembly or S-421 **TERMINATOR** Wedge Socket



UWO 422T
TERMINATOR
Wedge Only

- Sizes 4 Tons through 30 Tons available with Crosby's S1316A "Positive Locking" SHUR-LOC® hook which may be used for lifting personnel. Meets the intent of OSHA Rule 1926.1431(g)(1)(i)(A) and 1926.1501(g)(4)(iv)(B).
- Design Factor 4:1.
- The top swivel design on the UB500 assures the ball remains stationary if the Wireline spins.
- The swivel incorporates a sealed roller thrust bearing together with a grease fitting for easy lubrication.
- Each ball can be equipped with the new McKissick® US-422T

Wedge Socket which can be easily adjusted to fit various sizes of Wireline by changing the wedge (Ensure that correct wedge is used for selected Wireline size).

- All hooks used on UB500 Overhaul Balls (S320, S320N & S1316A) are forged from alloy steel. The S320 and S320N hooks come complete with latches.
- The S320 hook (PL latch) and the S320N hook (S4320 latch), with the proper latch attached, may be used for personnel lifting when secured with proper device (Bolt, nut and pin for the PL latch; Cotter pin for the S4320 latch). Meets the intent of OSHA Rule 1926.1431(g)(1)(i)(A) and 1926.1501(g)(4)(iv)(B).

Overhaul Ball Assembly

Optional US-422T Wedge Sockets

McKissick® UB500 Model No.	UB500 "E" Eye Hook Stock No.	UB500 "S" SHUR-LOC® Stock No.	Working Load Limit (Tons)	Weight Each (lbs.)	Wireline Size (in.)	Model No.	Wedge Socket Assy. Stock No.	Weight Each (lbs.)	Wedge Only Stock No.	Weight Each (lbs.)
MB4T35	1036000*	1036005	4	58	3/8	US4T	1044300	4.6	1047310	0.6
MB4T85	1036009*	1036018	4	102	7/16	US4T	1044309	4.6	1047301	0.6
MB4T150	1036027*	1036032	4	162	1/2	US4T	1044318	4.6	1047329	0.6
MB4T200	1036036*	1036041	4	201	1/2	US5T	1044327	8.5	1047338	1.0
MB7T85	1036045*	1036050	7	109	9/16	US5T	1044336	8.5	1047347	1.0
MB7T150	1036054*	1036063	7	170	5/8	US5T	1044345	8.5	1047356	1.0
MB7T200	1036072*	1036077	7	210	5/8	US6T	1044354	9.4	1047365	1.4
MB7T285	1036081*	1036086	7	321	3/4	US6T	1044363	9.4	1047374	1.4
MB10T150	1036090*	1036095	10	216						
MB10T200	1036099*	1036108	10	260						
MB10T285	1036117*	1036122	10	365	5/8	US6T	1044354	9.4	1047365	
MB10T350	1036126*	1036131	10	403	3/4	US6T	1044363	9.4	1047374	2.3
MB10T650	1036135*	1036140	10	718	7/8	US8T	1044404	20.8	1047425	2.4
MB12T150	1036144*	1036520	12	216	1	US8T	1044417	20.8	1047431	5.3
MB12T200	1036153*	1036529	12	258	1-1/8	US10T	1044426	46.5	1047440	6.0
MB12T285	1036171*	1036538	12	365	1-1/4	US10T	1044435	46.5	1047459	9.6
MB12T350	1036180*	1036547	12	403						10.5
MB12T650	1036189*	1036556	12	718						
MB15T200	1036198*	1036565	15	298						
MB15T350	1036207*	1036574	15	456						
MB15T650	1036216*	1036583	15	753						
MB15T1150	1036225*	1036592	15	1311						
MB20T200	1036234*	1036611	20	298	5/8	US8AT	1044372	17.5	1047383	3.1
MB20T350	1036243*	1036620	20	456	3/4	US8AT	1044381	17.5	1047392	3.4
MB20T650	1036252*	1036629	20	753	7/8	US8T	1044404	20.8	1047425	5.3
MB20T1150	1036261*	1036638	20	1311	1	US8T	1044417	20.8	1047431	6.0
MB25T350	1036270	1036647	25	533	1-1/8	US10T	1044426	46.5	1047440	9.6
MB25T650	1036279	1036656	25	865	1-1/4	US10T	1044435	46.5	1047459	10.5
MB25T1150	1036288	1036665	25	1421						
MB30T650	1036297	1036674	30	865						
MB30T1150	1036306	1036683	30	1421						

* Utilizes Crosby "N" style hooks with integrated latch. Replacement latch kit is S-4320. PL latch and S-4055 latch will not fit. Standard Crosby S-5 Thrust style swivels can not be used with UB500 Overhaul Balls. For replacement swivels, contact Crosby Customer Service.